

PRODUCT FLYER

VirtualBench All-in-One Instrument

CONTENTS

[VirtualBench All-in-One Instrument](#)

[Detailed View of VB-8054](#)

[Key Features](#)

[VirtualBench Accessories](#)

[NI-VirtualBench Application Programming Interface \(API\)](#)

[Learn More About VirtualBench](#)

[Hardware Services](#)

VirtualBench All-in-One Instrument

VB-8012, VB-8034, and VB-8054



- **Software:** Includes VirtualBench application, API support for LabVIEW and text-based languages, shipping examples, and detailed help files
- Up to 500 MHz mixed-signal oscilloscope with protocol analysis
- Arbitrary waveform generator with up to 40 MHz sine output
- 5 ½ digit DMM with 300 V input range
- Three-channel programmable DC power supply, up to 3 A
- Eight general-purpose digital I/O lines
- USB, Ethernet, and WiFi connectivity to Windows and Apple iPad software applications

Five Benchtop Instruments. One Unified Interface.

VirtualBench plays a key role in reducing the cost and footprint of test and measurement systems by consolidating five of the most commonly used instruments into one device without compromising the performance of each instrument. Combined with a modern software experience and simple programming interface, VirtualBench creates new efficiencies for engineers interacting with benchtop test equipment or developing low-cost automated test systems.



The VirtualBench hardware family currently consists of three models most easily designated by oscilloscope analog bandwidth: 100, 350, and 500 MHz. These models allow the VirtualBench family to serve a wide range of applications and price points in academic labs, hardware characterization/debug benches, and automated test systems.

Table 1. NI offers VirtualBench models ranging from 100 to 500 MHz of analog bandwidth.

	VB-8012	VB-8034	VB-8054
Mixed-Signal Oscilloscope (MSO) with SPI, I ² C, and Parallel Protocol Analysis			
Bandwidth	100 MHz	350 MHz	500 MHz
Channels	2 Analog, BNC	4 Analog, BNC	
	34 Digital	34 Digital	
Sample Rate	1 GS/s	1.5 GS/s/channel	2 GS/s/channel
Digital Multimeter			
Resolution	5 ½ Digits		
Input Range	300 V, Category II Isolation		
Measurement Functions	DC voltage, AC voltage, DC current, AC current, resistance, diode, continuity		
Arbitrary Waveform Generator			
Max Frequency	20 MHz (sine)		40 MHz (sine)
Waveform Types	sine, square, ramp/triangle, DC, arbitrary		
DC Power Supply			
Channel 1	0 to 6 V, up to 1 A	0 to 6 V, up to 3 A	
Channel 2	0 to -25 V, up to 0.5 A	0 to -25 V, up to 1 A	
Channel 3	0 to 25 V, up to 0.5 A	0 to 25 V, up to 1 A	
Digital I/O			
Channels	8 Channels		
Logic Levels	5 V compatible TTL input, 3.3 LVTTTL output		
General			
Connectivity	USB and WiFi	USB, WiFi, and Ethernet	
Size	10 in. x 7.5 in. x 2.9 in.	12 in. x 8 in. x 3.7 in.	
Interactive Software	Windows (7 SP1 and later), iPad (iOS 9 or later)		
Programming API	LabVIEW, ANSI C, and Python ¹		

¹Python wrapper is community-developed and not officially supported by NI

Detailed View of VB-8054



Key Features

Unified Software Interface

The VirtualBench application requires zero installation and can load automatically via Windows Autoplay when connected through USB. The integrated view of all five instruments allows you to import/export instrument configurations for easier replication of test conditions. VirtualBench also includes software capabilities like digital phosphor density maps for displaying multiple acquisitions simultaneously, XY mode for plotting channels against one another, and hands-free smart capture for automatic data capture of repeated stable waveforms. In order to future-proof any VirtualBench investment, free software and firmware updates are provided as new features are released. These features, in addition to the consolidated interface, help engineers streamline their approach for benchtop characterization and validation.




Figure 1: Export screenshots and data using one-click buttons or the hands-free smart capture feature.




Figure 2: Use measurement indicators to quickly characterize signals like this sine glitch. Choose to display common measurements like amplitude, max/min, RMS, period, and frequency indefinitely beneath the scope graph.




Figure 3: Simplify your measurements using intuitive configuration menus. The configured pulse width trigger reliably captures the displayed signal glitch.




Figure 4: Debug your system more easily by leveraging the built-in protocol decoder alongside the other instruments on the same time scale. The zero registered on the “DAC1” SPI line is likely the culprit of the glitch shown.

VirtualBench Accessories

VirtualBench ships with several accessories to enable common measurements as well as device connection with a PC or iPad.

- Oscilloscope probes (VB-8012: set of two, VB-8034/VB-8054: set of four)
- DMM probes (set of two)
- MSO logic analyzer 40-pin input cable
- Screw-terminal connectors
- NI screwdriver
- Wireless antenna
- USB cable with locking screw (2 m)
- Power cord

Optional Accessories

In addition to the standard, included accessories, NI has several optional accessories available that further extend the capabilities of VirtualBench.



Binding Post Adapter
(VB-8012 only)



Soft Carrying Case



Desktop Mounting Kit
(VB-8012 only)



Accessory Pouch



Rack Mount Shelf



Logic Analyzer Grabbers
(set of six)



DMM Alligator Clips, Spade
Connectors, & Spring
Hooks (P2 Probe Set)



FGEN BNC Male to
Micrograbber (87 cm)



BNC Cable, 50 Ohm Male
to Male (2 m)



USB Cable with Locking
Screw (1 or 2 m)

Hardware Services

All NI hardware includes a one-year warranty for basic repair coverage, and calibration in adherence to NI specifications prior to shipment. PXI Systems also include basic assembly and a functional test. NI offers additional entitlements to improve uptime and lower maintenance costs with service programs for hardware. Learn more at ni.com/services/hardware.

	Standard	Premium	Description
Program Duration	3 or 5 years	3 or 5 years	Length of service program
Extended Repair Coverage	•	•	NI restores your device's functionality and includes firmware updates and factory calibration.
System Configuration, Assembly, and Test ¹	•	•	NI technicians assemble, install software in, and test your system per your custom configuration prior to shipment.
Advanced Replacement ²		•	NI stocks replacement hardware that can be shipped immediately if a repair is needed.
System Return Material Authorization (RMA) ¹		•	NI accepts the delivery of fully assembled systems when performing repair services.
Calibration Plan (Optional)	Standard	Expedited ³	NI performs the requested level of calibration at the specified calibration interval for the duration of the service program.

¹This option is only available for PXI, CompactRIO, and CompactDAQ systems.

²This option is not available for all products in all countries. Contact your local NI sales engineer to confirm availability.

³Expedited calibration only includes traceable levels.

PremiumPlus Service Program

NI can customize the offerings listed above, or offer additional entitlements such as on-site calibration, custom sparring, and life-cycle services through a PremiumPlus Service Program. Contact your NI sales representative to learn more.

Technical Support

Every NI system includes a 30-day trial for phone and e-mail support from NI engineers, which can be extended through a [Software Service Program \(SSP\)](#) membership. NI has more than 400 support engineers available around the globe to provide local support in more than 30 languages. Additionally, take advantage of NI's award winning [online resources](#) and [communities](#).

©2019 National Instruments. All rights reserved. LabVIEW, National Instruments, NI, NI TestStand, and ni.com are trademarks of National Instruments. Other product and company names listed are trademarks or trade names of their respective companies. The contents of this Site could contain technical inaccuracies, typographical errors or out-of-date information. Information may be updated or changed at any time, without notice. Visit ni.com/manuals for the latest information.

10 December 2019